

# Generating Set

## TECHNICAL DATA SHEET

### SGT1875



Silent / Closed Type  
Image for illustration purposes only.

Prime Power*	Standby Power**	Voltage/Ph	Hz/rpm***	PF
1710kVA/1368 kWe	1875kVA/1500 kWe	400/3Ph	50/1500	0.8

#### Prime power\*

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period. A 10% overload is available for 1 hour in every 12 hours operation.

#### Standby power\*\*

Limited to 500 hours annual usage with an average load factor of 80% of the published Standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on Standby power. Available in 60HZ for all voltage ratings.\*\*\*

#### Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative humidity.

#### Diesel Generator Set

Engine Make /Model	PERKINS 4012-46TAG3A
Alternator Make /Model	Leroy Somer LSA51.2S55
Control Panel	DSE 7320
Base Frame / Silent Canopy	Robust Structure/ Corrosion Resistant
Circuit Breaker Type	3 Pole ACB (4P Available as optional)
Built in Base Fuel Tank Capacity	N/A
Battery	Maintenance free Lead Acid

Dimensions	Length (mm)	Width (mm)	Height (mm)	Weight (KG)
Close Type	12192	2438	2896	21580
Open Type	4850	2270	2465	11184

#### ENGINE SPECIFICATIONS

Engine Make Model	PERKINS 4012-46TAG3A
No. of Cylinders	12 60° Vee form
Cycle	4 Stroke
Aspiration	Turbocharged
Cooling Method	Water cooled
Governing Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	12.8:1
Displacement	45.84 litres
Bore/Stroke	160 x 190 mm
Dynamic Charging Alternator	

#### LUBRICATION SYSTEM

Oil Filter Type	Spin-On Full Flow
Total Oil Capacity	157.5 L
Oil Type	API-CH-4 or ACEA E5

#### AIR SYSTEM

Air Filter Type	PowerCore
Combustion Air Flow (PRP)	132.2 m <sup>3</sup> /min
Combustion Air Flow (ESP)	139.8 m <sup>3</sup> /min
Max Air Filter Intake Restriction	4 Kpa

#### COOLING SYSTEM

Total Coolant Capacity (L)	233 L
Cooling Fan Air Flow	TBD
Radiator Fan Load	81 Kw
Cooling system design	50°C
Heat Radiation to Room (PRP)	114 kW

#### Exhaust System

Muffler Type	Residential Grade
Max. Back Pressure	5 Kpa
Exhaust Gas Flow (PRP/ESP)	311.7/337.7 m <sup>3</sup> /min
Exhaust Gas Temperature	≤ 441 °C

#### Comply with Standards

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

#### Powered By:



#### Why SUN & ENERGY Generator Technology (SGT)?

When you are running a business every competitive advantage counts, choosing a right Generator Set can make all the difference to bottom line.

#### 1. Features & Benefits:


- SGT Gen set is powered by Perkins Engine, the world leader having over 85 years of innovation and excellence, with customers support in 182 countries from 3500 outlets.
- SGT Gen set is powered by Leroy Somer France Alternator, the Global number 1 in Alternators, with over 99 years of Experience, Having 120+ active patents, in over 40 countries and over 80 service centers.
- SGT Gen set is equipped with DSE controller, one of the world's top manufacturers in UK, having over 40 years of excellence, the most advanced and user friendly controller.
- Low fuel consumption, saving on fuel spend
- Compact and rugged design, saving on transport and storage cost
- Designed to occupy less space considering critical applications and cities where space is at a premium.
- Low noise and vibration, considering critical applications where noise level matters
- Easy maintenance and long service intervals, saving on maintenance cost
- Subject to rigorous tests including load acceptance, cooling, vibration and noise level prior shipment to customer.
- Simple to operate and environment friendly in worst ambient conditions
- Equipped with built-in fuel tank sufficient for 8 to 10 hours of operations.
- Fully Engineering wide range of optional accessories available.

(Contd.)

# Generating Set

TECHNICAL DATA SHEET

SGT1875




PERKINS Engine  
4012-46TAG3A



Leroy Somer  
LSA51.2S55



DSE7320 MKII  
AUTO START & AUTO MAINS



SGT ENCLOSURE/CANOPY

Sun & Energy Solar FZCO CEO  
Building Dubai Investment Park  
1 Dubai, U.A.E. +971509532031  
Sun & Energy

Engine Fuel System	
Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	472 L/hr
Fuel Consumption 100% PRP	425 L/hr
Fuel Consumption 75% PRP	310 L/hr
Fuel Consumption 50% PRP	209 L/hr

ALTERNATOR SPECIFICATIONS	
Alternator Make /Model	Leroy Somer LSA51.2S55
AVR Model	R 449
Number of Poles	4
Number of Winding Leads	6
Type of Bearing	Single Bearing
Insulation Class - Temp Rise	Cont. H - 125/40 C
Ingress Protection Rating	IP 23
Excitation System	AREP + PMI
Voltage Regulation	+/- 0.5%
Harmonic Coefficient THF	< 4%
Tel. influence TIF	< 50
Cooling air flow	2.5 m <sup>3</sup> /Sec

Controller Make & Model	DeepSea 320
Operation Mode	AMF
Display	Graphic Back-lit LCD (132x64) pixels
Ingress Protection Rating	IP65
Binary Inputs/Outputs	9/8
Analog Inputs	4
Measurement	Vac, A, Hz, kVA, kW, Vdc
Event Log	Alarms log, Hrs log
Communication	USB

Please refer to Controller Data Sheet for more details.

Enclosure Type	Acoustic & Weather Proof
Drainage	Fuel and Water Drainage Provision
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	RAL 9010 - Powder coated
Base frame RAL Color	RAL 9011 - Powder coated
Noise Pressure level @	TBD

Distributed & Serviced by:



Open Type Image for illustration purposes only.

## 2. WARRANTY POLICY:

- Noor Generator technology products has a warranty for all prime equipment, limited to 2000 running hours or 12 months warranty & For Standby equipment, Limited to 500 running hours or 12 months warranty whichever occur first against manufacturing defect.
- Wearing parts (filters), incorrect man-made operation, Back up Genset maintenance failures are excluded from the warranty policy
- For more details please refer to <https://www.sunergysolar.ae>

## 3. DOCUMENTAION

Operation and Maintenance Manual, GAD, Wiring Diagram & FAT Report are Accompanied with Genset.

## 4. OPTIONAL FEATURES

### A. Engine

- Heavy-Duty Air Filter
- Coolant Heater
- Lubricant Oil Heater
- Fuel and Water Separator
- Lube Oil Rotary Pump

### B. Alternator

- Anti Condensation Heater
- PMG + AVR
- Double Bearing Alternator
- RTDs For Bearing and Winding

### C. Cooling System:

- 55 degree Radiator
- Remote Radiator

### D. Control System:

- AMF / Parallel
- Remote Annunciators
- 4 p manual/Motorized Circuit breaker

### E. Automatic Transfer Switch (ATS):

- Contractor or Breaker type ATS
- Motorized changeover type ATS

### F. Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

### G. Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

### H. Available for voltages :

400/230V,480/277V,380/220V,440/254V,  
416/240V,220/127V, 208/120V